

• TRUSTED QUALITY SINCE 1921 •



**RUST-OLEUM®
DECORATIVE COLOR CHIPS**

DESCRIPTION AND USES

Rust-Oleum® Decorative Chips are designed for use with any one-part or two-part concrete floor coating. When sprinkled onto a freshly coated surface, these decorative chips bond to the wet film to become a permanent part of the coating.

Rust-Oleum Decorative Chips also help hide dirt and surface imperfections and can be used with water-based or solvent-based concrete coatings.

For use in: garages, carports, laundry rooms, basements, porches, patios, walkways and pool decks.

PRODUCTS

SKU	DESCRIPTION (1 lb.Bag)
301359	Gray Blend
312447	Tan Blend
312449	Glacier Gray Blend
301238	Mocha Blend
301357	Tan Blend (The Home Depot)
336054	Metallic Silver
337031	Metallic Gold
337035	Team Blend
358192	Micro Gray Blend

PRODUCT APPLICATION

Do not mix Decorative Color Chips into the coating. Apply concrete floor coating (sold separately) in 4'x4' sections. Immediately after completing the final roller passes, begin broadcasting the Decorative Color Chips onto the wet coating. Distribute the Decorative Color Chips by tossing them up into the air above the coating in an underhand manner. This allows the chips to drop directly down onto the surface of the coating. Avoid slinging the chips onto the coating with a sidearm throw.

IMPORTANT: Apply decorative color chips to wet paint only. Move on to the next 4'x4' section and continue until complete.

Note: Fresh paint can be applied over the loose chips that lay outside the previously painted area. For a high gloss finish, topcoat garage floors with EpoxyShield® Premium Series Clear Finish Or RockSolid® Clear Top Coat.

COVERAGE

Standard Chip Pattern – 250 square feet per bag
Heavy Chip Pattern – 125 square feet per bag

The technical data and suggestions for use contained herein are correct to the best of our knowledge, and offered in good faith. The statements of this literature do not constitute a warranty, express, or implied, as to the performance of these products. As conditions and use of our materials are beyond our control, we can guarantee these products only to conform to our standards of quality, and our liability, if any, will be limited to replacement of defective materials. All technical information is subject to change without notice.